


GULF AC AXIAL FAN

GA1092 GA2092


92x92x25.4mm BETA




DESIGN FEATURES

- *BEARING SYSTEM: SLEEVE BEARING & BALL BEARING
- *IMPELLER: PLASTIC WITH FIBER GLASS FILLED UL 94V-0
- *HOUSING: DIE CAST ALUMINUM & ZINC
- *MOTOR: SHADED POLE, IMPEDANCE PROTECTED
- *CONNECTING: TERMINAL & WIRE LEADS
- *SPEED: S-1 HIGH SPEED TYPE
S-2 MEDIUM SPEED TYPE
S-3 LOW SPEED TYPE
- *OTHER VOLTAGE: 24 ,48, 100, 380AC (50/60Hz) ARE AVAILABLE

DIMENSIONS:MM



PERFORMANCE



SPECIFICATIONS

Specifications are subject to change without notice

MODEL NO.	VOLT (VAC)	FREQUENCY (HZ)	AIR (CFM)	VOLUME (M ³ /MIN)	CURRENT (A)	POWER (W)	SPEED (RPM)	STATIC PRESSURE (INCH-H ₂ O)	NOISE (dBA)
GA1092HBL	110/120	50/60	30/36	0.85/1.00	0.21/0.20	19/17	2400/2800	0.16/0.20	35/37
GA2092HBL	220/240	50/60	30/36	0.85/1.00	0.10/0.09	19/17	2400/2800	0.16/0.20	35/37
GA1092MBL	110/120	50/60	25/28	0.71/0.77	0.07/0.06	12/10	2100/2400	0.13/0.14	28/30
GA2092MBL	220/240	50/60	25/28	0.71/0.77	0.06/0.05	12/10	2100/2400	0.13/0.14	28/30
GA1092LBL	110/120	50/60	21/22	0.62/0.60	0.06/0.05	8/6	1700/1900	0.10/0.09	22/24
GA2092LBL	220/240	50/60	21/22	0.62/0.60	0.05/0.04	8/6	1700/1900	0.10/0.09	22/24



海灣電氣有限公司 TEL:886-7-5219966
飛安電氣有限公司 FAX:886-7-5213535